




ART-245 2001-2007 TOYOTA SEQUOIA FRONT FRAME SECTION

IMPORTANT: Read and understand the General Instructions
Before Installing SafeT-Cap® Frame Repair Kits

Installation Instructions

- 1)** Jack up the front & rear of vehicle and support it on properly rated jack stands. Make sure the center of vehicle is fully accessible.
- 2)** If replacing sway bar mount remove the front sway bar from the frame by disconnecting the sway bar links, then unbolting the sway bar mounts on both driver and passenger side. Inspect sway bar bushings, replace if necessary.
- 3)** If you are repairing both sides, cut & repair one side at a time keeping one side assembled as a reference / measuring point.
- 4)** Remove any brackets, wiring, exhaust, and fuel/brake lines from the frame and move them out of the way noting their location. You may need to drill holes in the frame kit to reattach fuel/brake line clips after installation.
- 5)** The ART-245 has 2 cut lines where the front cab mount is mounted. Determine if your original front cab mount needs to be replaced or if the metal behind the cab mount is rotted. If the cab mount is not being replaced or removed, then remove the plate by continuing the cut lines so the frame kit is notched around the cab mount.

- 6)** Only if removing sway bar mount measure the location of the original sway bar mount, then cut the sway bar mount from the frame. Also remove any rusted and corroded sections. Note: It is best to remove the very bottom of the original frame within the covered area to allow the drain hole to drain properly.
- 7)** Slide the SafeTCap® frame repair kit over the frame from underneath and evenly space the frame kit around the cab mount and the Transmission cross member end. Mark the outline of the frame repair kit on the frame, then remove the kit.
- 8)** Prep the repair area for welding by grinding the frame down to clean, bare metal along the marked outline on both the inner and outer sides of the frame. Remove any rust or debris from inside the frame using a needle scaler.
- 9)** Slide the frame repair kit back over the frame and use large C-clamps to firmly clamp ART-245 to the frame. Use welding clamps to tighten any gaps on the sides. Then, tack weld the frame repair kit to your frame.
- 10)** The ART-245 frame kit comes with a replacement sway bar mount. Using the measurements taken earlier, tack weld the new sway bar mount to the frame. Before fully welding the new sway bar mount double check its placement.
- 11)** Check measurements and door gaps to make sure the vehicle has stayed straight, then, weld all edges 100%.
- 12)** Prime or rust proof the repaired area, then re-attach any brackets, wiring and/or brake lines back to the frame and re-install the sway bar.